



MB07

RocketRibbon™ Cable Slitter

Introducing an innovative cable slitter engineered with a precision factory-set blade depth to quickly and easily access fiber subunits and ripcords in Corning RocketRibbon™ cables.

Features

- Precision factory-set blade depth ensures no fiber damage
- Shielded blade promotes safe operation and prevents injuries
- Compatible with Corning RocketRibbon™ 1728, 864 & 432 Cables
- Single brass guide wheel reduces drag while performing longitudinal cuts
- Ergonomic handle provides greater leverage during ring cuts and finger grip provides comfortable hand positioning during longitudinal cuts
- Rugged aluminum tool body and high performance tool steel blade ensures longevity
- Efficiently performs ring and longitudinal cuts on cable mid-span or end no blade adjustment necessary

Additional Information

| MODEL | PART # | DESCRIPTION | CABLE COMPATIBILITY | DIMENSIONS | WEIGHT |
|-------|-----------|---|--|--|------------------------|
| MDOZ | MB07-7000 | MB07 RocketRibbon™ Cable Slitter | Corning RocketRibbon™ 1728, 864 & 432 Cables | 7.7" x 2.0" x 1.375" (195.6 x 50.8 x 34.9 mm) | 11.12 oz (315.25 g) |
| MB07 | MB07-7500 | Replacement Blade Kit (Blade, Block, Screw, Instruction Sheet & Wrench) | Corning RocketRibbon™ 1728, 864 & 432 Cables | N/A | N/A |



Convenient markings easily identify blade position settings to perform longitudinal and ring cuts.




Ergonomic tool handle provides additional leverage during ring cutting operations.




Unique finger grip shields the guide wheel and reduces hand strain during longitudinal cuts.



Precision, factory-set blade depth ensures accurate slitting operations without fiber damage.









Make Cable Preparation Easier

With Additional Ripley® Products



CFS-3

3-Hole Fiber Optic Wire Stripper

- Three hole design efficiently removes 1.6 mm to 3 mm fiber jackets & buffers down to the 125 micron bare fiber
- Manufactured to precise tolerances to ensure clean, smooth strips every time
- Compliant & comfortable thermoplastic elastomer handle grips

| MODEL | PART # | WIRE SIZE Ø |
|-------|--------|-------------|
| CFS-3 | 81300 | 1.6 to 3 mm |



KS-1

Fiber Optic Kevlar® Shears

- Ideal for cutting Kevlar® strength fibers in fiber optic cable
- Lightweight & ergonomic design
- Micro-serrated blade reduces slippage for precise cuts

| MODEL | PART # | ITEM DESCRIPTION |
|-------|--------|--|
| KS-1 | 80671 | Fiber Optic Kevlar® Shears |
| KS-1 | 80665 | Fiber Optic Kevlar® Shears & Nylon Carrying Pouch |



FTS Series

Fiber Tube Scorers

- Precise, one-step buffer tube scorer
- Fixed, hardened carbon steel blade requires no adjustments
- FTS body comprised of strong & resilient acetal polymer

| MODEL | PART # | TUBE SIZE | WALL THICK. |
|-------------------|--------|-----------------------------------|-------------------------------------|
| FTS-005 (Red) | 80990 | Up to 0.079" Up to 2 mm | 0.005" to 0.010" 0.13 to 0.25 mm |
| FTS (Yellow) | 80980 | 0.062" to 0.236" 1.6 to 6.0 mm | 0.010" to 0.020" 0.25 to 0.50 mm |
| FTS-035 (Blue) | 80985 | 0.062" to 0.236" 1.6 to 6.0 mm | 0.039" to 0.051" 1.0 to 1.3 mm |



RCS-114 & RCS-158

Round Cable Strippers

- Designed for fast, safe & precise removal of PE, PVC, rubber & other jacket materials
- Spring-loaded cable brace firmly secures cable against the blade for controlled cutting action
- Durable blade performs rotary & spiral type cuts

| MODEL | PART # | CABLE SIZE Ø |
|---------|--------|-----------------------------------|
| RCS-114 | 37140 | 0.178" to 1.14" 4.5 to 29.0 mm |
| RCS-158 | 37145 | 0.75" to 1.58" 19.0 to 40.0 mm |
| CB231 | 37150 | Replacement Blade |

