



# MB11

## Heavy Duty Armored Shaving Tool 6-26mm


Shaves jacket off steel strength members for use with attachment cleats and to provide easy access to internal armor.



### Features

- Ergonomic handle for reduced fatigue and easier force generation
- L-Bracket to apply clamping force on cable, ensuring a reliable cut
- Use wing-knob to adjust cable setting, **NO SCREWDRIVER NECESSARY!**
- Tool body accurately aligns blade for optimum shaving angle
- Tool-free blade replacement with captive hardware, **NO SCREWDRIVER NECESSARY!**
- Offset block allows blade to be reversed for double blade life. (2X)
- **Compatible with standard Utility Knife Blades**
- Reinforced polymer body with metal inserts for toughness and wear resistance

Part #	Item description	Cable compatibility	Cable size
MB11-7002	Heavy Duty Armored Shaving Tool	Corning RocketRibbon 12F - 864F	0.33" - 0.87" (8.38mm - 22.1mm)
		OFC AccuRoll Dry Core Armored (Metallic) 12F - 864F	0.39" - 0.81" (10mm - 20.6mm)
		Other armored cables w/ steel strength members	0.25" - 1.02" (6mm - 26mm)
		Thick walled tube, thin walled microduct. Compatibility is best tested on sample cable	0.25" - 1.02" (6mm - 26mm)



Open the tool by releasing the yellow wing-knob, **no tool required**

Set the tool on the cable, using the spacing barrel to set the optimal blade angle

Draw the tool down the cable, opening an access window to the strength member

The shaving operation only uses half the blade. Flip the blade for double blade life. Release the thumb knob to slide the blade out. **No tool required. Compatible with standard utility knife blades**

For more information or to locate your nearest authorized Ripley® distributor, visit [www.ripley-tools.com](http://www.ripley-tools.com) or call **1 (800) 528-8665** to speak with a customer service representative.



A proud member of the Hubbell family.